

Manufacture and distribution of high quality floor cleaning and care products, as well as cleaning systems

Production · Logistics

Schutz Group
8701 Torresdale Ave #P
Philadelphia, PA 19136, USA

Telefon:

+1 877 272 4889 x3

Fax: +1 877 272 4889

info@dr-schutz.us · www.dr-schutz.us

Product-Information

Turbo Strip



1. Product description

Express-stripper with fast-working formula. Powerfully and thoroughly removes the care-film of gloss emulsions, even tackling stubborn remains of old care-products, whether there are several layers of these or also heavily careworn covering surfaces. Works into the surface very quickly, using a formula which minimizes odor. For professional users in larger buildings.

2. Areas of application

Floor coverings made of synthetic materials (PVC, CV, polyolefin), linoleum and rubber coverings (*). Not suitable for floors sensitive to solvents (e.g. asphalt-tiles), nor for floors which have been coated with professional sealants (e.g. Waxnomor). Please observe the care instructions relating to specific floor coverings.

(*) Always check first, make sure that the color and material are resistant, by trying out an unobtrusive area !

3. Application

Coarse dirt should first be swept or vacuumed away. Dilute Turbo Strip with water in a ratio of between 1:1 and 1:5 (depending on resistance of the care-film). Spread the diluted cleaner over the floor covering and let it soak in for about 5-15 minutes. Then work away at the covering surface with a scrubbing brush, or with Padmaster, or Monodisc machine SRP (using the appropriate pad, or scrubbing-brush attachment). Remove the soiled liquid with wet-suction (e.g. spray suction with hard floor adapter, Premium F1/F2), or rubber squeegee and absorbent wide-mop, and carefully wash the floor with clear water until the surface has been completely neutralised.

Please note: Do not let Turbo Strip dry out on the floor, therefore work in sections at a time. Before stripping, check the covering for color and material consistency at a place that will not be noticed. Do not moisten sensitive surfaces (e.g. wood, metal, furnishings, lacquered and sealed surfaces) with the cleaning mixture.

Consumption: 2-6 liters per 1000 sq. ft (dilution of 1:1 up to 1:5)

4. Technical Data

pH-value: approx. 10.0 (concentrate)

Substances contained: less than 5% non-ionic tenside. Contains fragrances, LIMONENE, amine, solvents.

Giscode: GG 60 (Productcode for cleaning and care products)

Turbo Strip is subject to regulations concerning hazardous substances and displays the hazard symbol "X_i" and includes hazard information "Causes irritation to the eyes." Avoid any skin or eye contact with the stripper. Only use in well-ventilated areas.

Store Turbo Strip in closed original containers, in a cool and dry place. Keep tightly closed and out of the reach of children.

5. Container sizes

10 liters - canister

The information above is given to the best of our knowledge and according to the latest state of technology. Therefore, if the procedural recommendations are carefully followed, as well as our advice regarding the materials, specifically for these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility and this does not release you from an obligation to check our products on delivery to ensure that they are suitable for the purpose and procedures intended. Our notes and advice are therefore not legally binding and cannot be used against us as grounds for liability – which also includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.

