

WATERBORNE FINISHES

PRODUCTOS DE ACABADO CON BASE DE AGUA

FORTICO SEALER NF

A filling, water-based one component primer for roller application. FORTICO SEALER can be used as a primer for parquet to finish with waterborne finishes from the FORTICO range of products. FORTICO SEALER is recommended for floor heating, exotic wood types and cork.

- » Prevents side-bonding effect and minimizes roughening of the fibre.
- » Recommended for tropical wood species and for places with floor heating.

FORTICO SEALER NF

Base fijador a base de agua de un solo componente para aplicar con rodillo. FORTICO SEALER se puede utilizar como base para el parqué consiguiendo acabados al agua en todos los productos de la gama FORTICO. Se recomienda usar FORTICO SEALER para suelos radiantes, tipos de madera exótica y el corcho.

- » Evita el efecto de adhesión lateral y minimiza la rugosidad de la fibra.
- » Recomendado para maderas tropicales y para lugares con calefacción de suelo.



2,5L



PREPARATION

Make sure that all old finish coats are completely removed and that the wood is free from dust and other dirt. Can be used on sanded, planed, and brushed wood.

APPLICATION

Stir and shake well before use. Apply generously with a roller or brush.

FINISHING

Finish FORTICO SEALER with a waterborne finish from the FORTICO product line.

TECHNICAL DATA

Product type:	waterborne
Cleaning:	water
Viscosity:	+/-30 sec - DIN 4 mm
Solid content:	+/- 35%
Coverage:	85 - 125 sq.ft/L per coat
Drying times:	dust dry: after 45 min. to 1 hour sandable after 2 to 3 hours
Sanding grit:	P 120-150
Storage/transport:	between 5°C and 25°C
Disposal:	dispose of residue and empty packaging in accordance with local ordinances.

DATOS TÉCNICOS

Tipo de producto:	base agua
Limpieza:	agua
Viscosidad:	+/-30 sec - DIN 4 mm
Componentes sólidos:	+/- 35 %
Rendimiento:	85 - 125 sq.ft/Litro por capa
Tiempo de secado:	antiadherente al polvo: después de 45 min. a 1 hora se puede lijar: después de 2 a 3 horas
Grano de lijado:	P 120-150
Almacenamiento/transporte:	entre 5°C y 25°C
Tratamiento de residuos:	deseche los residuos y envases vacíos de acuerdo con sus ordenanzas locales.

IMPORTANT INFORMATION ⚠

Only use non-corrosive materials. Clean all materials with water immediately after use. For exotic types of wood, the finishing should be tested in advance. For industrial application, please consult Ciranova® technical support. **Water-based products can develop skins after contact with air. Filter beforehand, if necessary.**