

# MAINTENANCE FOR OILED FINISHES

## MANTENIMIENTO DE LOS SUELOS CON ACABADOS CON BASE DE ACEITE

### MAINTENANCE OIL

#### MATT - SATIN - WHITE

Universal fast-drying oil for the maintenance of oiled wooden surfaces. Dull or heavily used wood can be refreshed with Ciranova® maintenance oil. Regular application may avoid expensive and time-consuming renovations.

- » Universal maintenance oil
- » Also suitable for UV-oiled wood
- » Available in extra matte and satin

### ACEITE DE MANTENIMIENTO

#### MATE - SATINADO - BLANCO

Aceite de secado rápido universal para el mantenimiento de superficies de madera aceitadas. Maintenance Oil de Ciranova® renueva suelos deslustrados o desgastados. Aplicarlo regularmente puede evitar renovaciones costosas tanto en tiempo como en dinero.

- » Aceite de mantenimiento universal
- » También apto para suelos con aceitado UV
- » Disponible en extramate y satinado

#### TECHNICAL DATA

|                    |                                                                             |
|--------------------|-----------------------------------------------------------------------------|
| Product type:      | Solvent-based                                                               |
| Viscosity:         | +/- 20-25 sec - DIN 4mm                                                     |
| Solid content:     | +/- 29%                                                                     |
| Gloss level:       | Matte Satin                                                                 |
| Cleaning:          | Cleaning Thinner Ciranova®                                                  |
| Number of colors:  | Clear and white                                                             |
| Sold by case:      | 6 x 1 L                                                                     |
| Coverage:          | 450-650 sq.ft./L / 1700 - 2460 sq.ft./gal                                   |
| Drying times:      | +/- 4 hours                                                                 |
|                    | Lightly walkable after 12 hours.                                            |
| Storage/transport: | between 5°C and 25°C                                                        |
| Disposal:          | Dispose of residue and empty packaging in accordance with local ordinances. |

#### DATOS TÉCNICOS

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| Tipo de producto:          | base de disolvente                                                           |
| Viscosidad:                | +/- 20-25 s - DIN 4 mm                                                       |
| Materias sólidas:          | +/- 29 %                                                                     |
| Grado de brillo:           | Mate Satinado                                                                |
| Limieza:                   | Cleaning Thinner Ciranova®                                                   |
| Número de colores:         | Incoloro y blanco                                                            |
| Vendido por caja:          | 6 x 1 L                                                                      |
| Rendimiento:               | 450-650 sq.ft./L / 1700 - 2460 sq.ft./gal                                    |
| Tiempo de secado:          | +/- 4 horas                                                                  |
|                            | Pueden colocarse cargas encima tras 12 horas.                                |
| Almacenamiento/transporte: | entre 5 °C y 25 °C                                                           |
| Desecho:                   | Deseche los residuos y envases vacíos de acuerdo con sus ordenanzas locales. |



1L



#### PREPARATION

Before applying the product: clean the surface with intensive cleaner (remove soap residue), rinse with water, let surface dry, make it dust free.

#### APPLICATION

For wooden floors: Apply a thin and even layer of the maintenance oil, let it settle for a few minutes and then rub or buff it dry with a white pad. For smaller surfaces: apply the product with a lint-free cloth and remove any excess product.

#### MAINTENANCE

It is recommended to follow the Ciranova® Maintenance program to keep the wood in optimal condition. For regular maintenance, we recommend Ciranova® Flooring Soap. For periodic maintenance, use Ciranova® Maintenance Oil. In case of heavy soiling, first use Ciranova® Intensive Cleaner.

#### IMPORTANT INFORMATION ⚠

Dried oil residue is self-igniting. Used pads and clothes must be submerged in water after use. The final color depends on the wood type, sanding, and the amount applied. **That is why it is recommended to always test the color beforehand!**