

WATERBORNE FINISHES

PRODUCTOS DE ACABADO CON BASE DE AGUA

WOODLOOK PLUS

WOODLOOK PLUS is an invisible, 35% Bio-based, environmentally friendly, water-based PU impregnating oil for parquet and wooden furniture. The wood will have a slightly bleached and ultra matte appearance. WOODLOOK PLUS is non-yellowing and has anti-slip properties.

- » Ultimate invisible finish
- » Slightly bleached appearance
- » Very easy to apply
- » Non-yellowing

WOODLOOK PLUS

WOODLOOK PLUS es un aceite invisible de impregnación de poliuretano al agua, respetuoso con el medio ambiente y elaborado en un 35 % con productos biológicos, ideal para parquet y muebles de madera. La madera tendrá un aspecto ligeramente decolorado y ultramate. WOODLOOK PLUS no amarillea y cuenta con propiedades antideslizantes.

- » Acabado invisible definitivo
- » Aspecto ligeramente decolorado
- » Muy fácil de aplicar
- » No amarillea

TECHNICAL DATA

Product type:	waterborne
Cleaning:	Water
Gloss level:	Invisible
Viscosity:	+/-25 sec - DIN 4mm
Solids content:	+/- 31%
Coverage:	125-150 sq.ft./L per coat / 470 - 560 sq.ft./gal
Drying times:	Dust dry: after 20 to 30 minutes Sandable: after 4 or 6 hours Lightly walkable: after 24 hours Fully cured: after +/- 7 days
Sanding grit:	P 120-150
Storage/transport:	between 5°C and 25°C
Disposal:	Dispose of residue and empty packaging in accordance with local ordinances.

DATOS TÉCNICOS

Tipo de producto:	Al agua
Limpieza:	Agua
Grado de brillo:	Invisible
Viscosidad:	+/-25 sec - DIN 4mm
Sustancias sólidas:	+/- 31%
Rendimiento:	125-150 sq.ft./L per coat / 470 - 560 sq.ft./gal
Tiempos de secado:	Antiadherente al polvo: después de 20 a 30 minutos Se puede lijar: después de 4 a 6 horas Soporta peso ligero: después de 24 horas Totalmente endurecido: después de +/- 7 días
Grano de lija:	P 120-150
Almacenaje/transporte:	entre 5°C y 25°C
Desecho:	Deshacerse de los residuos y envases vacíos de acuerdo con la normativa local.



OPTIONAL
HARDENER



PREPARATION

Make sure all prior coatings are completely removed and the wood surface is free from dust and other contamination. Can be used on sanded, planed and brushed wood.

APPLICATION

WOODLOOK PLUS can be used both as primer and as finishing coat. It can be applied in three coats. Stir thoroughly before use and do not dilute. Apply the product using a roller, brush or spray gun. A short-pile roller is recommended (microfiber 4-6mm). Contact Ciranova® technical support for spray application. Apply the first coat in the direction of the wood. After 4-6 hours, apply a second coat in the same way as the first coat. Let dry for 12-24 hours and afterwards do an intermediate sanding using grit 180-220, then apply the third coat. **OPTIONAL: A HARDENER FORTICO (10%) CAN BE ADDED TO INCREASE THE CHEMICAL AND MECHANICAL RESISTANCES.**

FINISHING

WOODLOOK PLUS can be used both as primer and as a finishing coat.

MAINTENANCE

Regular maintenance with Ciranova® Hard Floor Fresh. Use UNICARE X-MATT for periodic maintenance. Ciranova® Hard Floor Cleaner is used for cleaning highly soiled floors and to remove old layers of polish.

IMPORTANT INFORMATION ⚠

Only use non-corrosive materials. Clean all materials with water immediately after use. For exotic types of wood, the finishing should be tested in advance. **For industrial application, please consult Ciranova® technical support. Water-based products can develop skins after contact with air. Filter beforehand, if necessary.**