

OILS ACEITES

WORKTOP OIL

Ciranova® WORKTOP OIL is the perfect finish for wooden worktops, cutting boards, furniture, and tables on which food is prepared. The WORKTOP OIL provides natural, waterrepellent protection. Ciranova® WORKTOP OIL has been tested in line with the 1935/2004 standard and, after drying, meets the requirements to be used on wood that comes into contact with food. Ciranova® WORKTOP OIL is made from naturalwaxes, modified oils, and vegetable and renewable fatty acids.

- » Very suitable for wooden worktops, cutting boards, and tables.
- » Provides a water and stain-resistant finish.
- » Tested according to the NO 1935/2004 article 3C standard.
- » Easy to apply.

WORKTOP OIL

WORKTOP OIL de Ciranova® es el acabado perfecto para encimeras de madera, tablas de cortar, muebles y mesas en las que se preparan alimentos. WORKTOP OIL proporciona una protección natural repelente al agua. Ciranova® WORKTOP OIL ha sido probado de acuerdo con el estándar 1935/2004 y, después del secado, cumple con los requisitos para ser utilizado en la madera que entra en contacto con los alimentos. Ciranova® WORKTOP OIL está hecho de ceras naturales, aceites modificados y ácidos grasos vegetales y renovables.

- » Muy adecuado para encimeras de madera, tablas de cortar y mesas.
- » Proporciona un acabado resistente al agua y a las manchas. Probado de acuerdo con la norma NO 1935/2004 del artículo 3C.
- » Fácil de aplicar.

TECHNICAL DATA

Type of product:	Solventborn
Cleaning:	Ciranova® cleaning thinner
Gloss level:	Matt & Satin
Viscosity:	+/-50 sec - DIN 4mm
Solid substances:	+/- 46%
Coverage:	320 - 375 sq.ft/liter per coat
Drying times:	Paintable: after +/- 6 hours Fully cured after +/- 7 days
Sanding grit:	P 120-150
Storage/transport:	between 5°C and 25°C
Disposal:	Dispose of residues and empty packaging in accordance with local regulations.

DATOS TÉCNICOS

Tipo de producto:	Base disolvente
Limpieza:	Disolvente de limpieza de Ciranova®
Sustancias sólidas:	Mate y satin
Viscosidad:	+/-50 sec - DIN 4mm
Sustancias sólidas:	+/- 46%
Rendimiento:	320 - 375 sq.ft/litro por capa
Tiempos de secado:	Repintable: después de +/- 6 horas. Curado completo: después de +/- 7 días
Grano de lija:	P 120-150
Almacenaje/transporte:	entre 5°C y 25°C
Desecho:	Deshacerse de los residuos y envases vacíos de acuerdo con la normativa local.



500 ml



PREPARATION

Ensure that all old finishing layers have been completely removed and that the surface is free of dust and other contaminants.

APPLICATION

Shake the WORKTOP OIL well before use. You can easily apply the Ciranova® WORKTOP OIL with a lint-free cloth in the direction of the wood grain. For larger surfaces, you can use a brush. Apply a thin layer and let the oil soak into the wood for 15 minutes, then wipe the surface dry with a lint-free cloth. For hard woods such as oak, at least 2 coats are required. Multiple coats can be used for soft woods.

DRYING TIME

Can be painted over after +/- 6 hours. Drying times depend on the amount applied, ambient temperature, humidity, and ventilation.

FINISHING

Use Ciranova® WORKTOP OIL as both a base and final coat.

MAINTENANCE

Apply a new coat of WORKTOP OIL Ciranova® regularly to ensure permanent water-repellent protection. In the event of heavy soiling, use the Ciranova® intensive cleaner to clean the wood first. WORKTOP OIL is only fully cured after +/- 7 days. Do not treat with water or maintenance products.

IMPORTANT INFORMATION ⚠

Dried oil residue is self-igniting. **Used pads and clothes must be submerged in water after use.**